

793nm, 200 μ m, Conduction-Cooled, Single Bar, Fiber-Coupled Module

Features

- High coupling efficiency
- High brightness
- Sealed housing
- Standard fiber coupling (HP-SMA) for 200 μ m NA 0.22



Device Specification

Optical Parameters ¹	Units	
Center Wavelength Range ³	nm	793
Center Wavelength Tolerance	nm	± 3
Output Power ²	W	32
Spectral Width (FWHM)	nm	4
Slope Efficiency	W/A	>0.80
Wavelength Temp. Coefficient	nm/ $^{\circ}$ C	~ 0.27

Fiber Parameters		
Numerical Aperture ⁵	NA	0.22
Fiber Core Diameter	μ m	200
Fiber Connector		HP-SMA 905 with Free Standing Fiber Tips

Electrical Parameters ¹		
Power Conversion Efficiency	%	>40
Threshold Current (I_{TH})	A	<11
Operating Current (I_{OP})	A	<55
Operating Voltage (V_{OP})	V	<1.9

Thermal Parameters		
Operating Temperature ^{3, 4}	$^{\circ}$ C	+20 to +30
Storage Temperature ⁴	$^{\circ}$ C	0 to +55
Recommended Heatsink Capacity	W	>70

Optional

True unpolarized output is available as an option.

¹Data at 25 $^{\circ}$ C cold plate temperature.

²Reduced lifetime if used above nominal operating conditions.

³Others available upon request.

⁴A non-condensing environment is required for storage and operation below the ambient dew point.

⁵Low numerical aperture option available at 0.12 for 400 μ m.

