

**Features**

- Free standing fiber tip
- High centricity




**Device Specification**

Parameter	Units	
Connector Type		SMA 905 both sides, with Free Standing Fiber Tip.
Ferule Diameter	mm	3.167 – 3.172
Outer Diameter <small>(Largest Diameter at Connector)</small>	mm	9.5
Cable Diameter	mm	7.6
Fiber Length <sup>1</sup>	m	2 or 5 ± 0.1
Numerical Aperture	NA	0.22 ± 0.02
Core Diameter	µm	200 ± 4
Cladding Diameter	µm	280 ± 5
Centricity	µm	<6
Long Term Bending Radius (Coil Radius)	mm	min. 44
Short Term Bending Radius	mm	min. 22

<sup>1</sup>Others on request.

**Dimensions**



**U.S. CFR Regulation**

The manufacturer and subsequent sale of laser equipment is under the guidelines governed by the U.S. Center for Devices and Radiological Health (CDRH). In accordance to those guidelines, specifically Subchapter J of the Radiation Standards, 21 CFR, the diode laser is registered as a CLASS 4 laser product.

**European Commission**

In accordance to EN 60825, Safety of Laser Products, the diode laser is registered as a CLASS 4 laser product.

Products specifications are subject to change without notice. For handling precautions, please reference the general handling instruction manual. For additional information, please contact your local sales representative or visit our website at [www.dilas-ils.com](http://www.dilas-ils.com).

**DILAS Industrial Laser Systems**

a division of DILAS Diodenlaser GmbH  
Galileo-Galilei-Straße 10  
55129 Mainz  
Germany

Phone: +49 (6131) 9226 400  
Fax: +49 (6131) 9226 444  
Email: [sales@dilas-ils.com](mailto:sales@dilas-ils.com)  
[www.DILAS-ILS.com](http://www.DILAS-ILS.com)